

## SILASTIC(R) 81-R CURING AGENT

## 1. IDENTIFICATION OF THE SUBSTANCE AND OF THE COMPANY

<b>Trade name</b>	:	SILASTIC(R) 81-R CURING AGENT		
<b>Company</b>	:	Dow Corning S.A. Parc Industriel - Zone C B-7180 Seneffe Belgium		
<b>Service</b>	:	Dow Corning Central Europe	Tel: +49 6112371	Fax: +49 611237609
		Dow Corning Northern Europe	Tel: +44 1676528000	Fax: +44 1676528001
		Dow Corning Southern Europe	Tel: +33 472841360	Fax: +33 472841379
<b>Emergency Phone Number</b>	:	Dow Corning (Barry U.K. 24h)	Tel: +44 1446732350	
		Dow Corning (Wiesbaden 24h)	Tel: +49 61122158	
		Dow Corning (Seneffe 24h)	Tel: +32 64 888240	

## 2. COMPOSITION / INFORMATION ON INGREDIENTS

**Chemical characterization:** Organotin compound

**Hazardous Ingredients:**

Name	CAS-No.	EINECS/ ELINCS No.	Conc. (% w/w)	Classification	
Tetrapropyl orthosilicate	682-01-9	211-659-0	25.0	Xi	R36/38
Trimethoxyphenylsilane	2996-92-1	221-066-9	11.0	Xn	R22
Dibutyltin dilaurate	77-58-7	201-039-8	3.0	Xn N	R20/21/22 R51/53
Tetramethyl orthosilicate	681-84-5	211-656-4	1.0	T	R25
Methanol	67-56-1	200-659-6	0.4	T	R39/23/24/25 R23/24/25
Cyclohexyltrimethoxysilane	-	Exempt or not available	0.2	Xn N	R20/22 R51/53

## SILASTIC(R) 81-R CURING AGENT

### 3. HAZARDS IDENTIFICATION

The principal hazards of the product as supplied are:

Flammable.

Harmful if swallowed.

Irritating to eyes and skin.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

### 4. FIRST AID MEASURES

- On contact with eyes** : Flush with water. Obtain medical attention.
- On skin contact** : Wipe off and wash with soap and water. If skin irritation persists, get medical attention.
- If inhaled** : Remove to fresh air.
- On ingestion** : Obtain medical attention.

### 5. FIRE FIGHTING MEASURES

- Suitable extinguishing media** : Carbon dioxide, foam, dry powder or fine water spray. Water can be used to cool fire exposed containers.
- Unsuitable extinguishing media** : None known.
- Hazards during fire fighting** : Electrostatic charges may be generated during transfer of product from its container. Ensure that all equipment is electrically earthed.
- Special protective equipment/procedures** : A self-contained respirator and protective clothing should be worn. Keep containers cool with water spray until well after the fire is out. Determine the need to evacuate or isolate the area according to your local emergency plan.
- Hazardous Combustion Products** : Silica. Carbon oxides and traces of incompletely burned carbon compounds. Formaldehyde. Metal products.

### 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions** : Wear proper protective equipment.
- Precautions to protect the environment** : Do not empty into drains. Prevent from spreading or entering into drains, ditches or rivers by using sand, earth or other appropriate barriers.
- Methods for cleaning up** : Determine the need to evacuate or isolate the area according to your local emergency plan. Eliminate all possible sources of ignition. Very large spills should be contained by bunding, etc... procedures. Mop, wipe or soak up with absorbent material and place in a container with a lid. The spilled product produces an extremely slippery surface.

## SILASTIC(R) 81-R CURING AGENT

### 7. HANDLING AND STORAGE

- Advice on safe handling** : Avoid skin and eye contact. Do not breathe vapour. Do not ingest. General ventilation is required. Local ventilation is recommended.
- Advice on storage** : Store in a flameproof, well ventilated area. Electrostatic charges may be generated during transfer of product from its container. Ensure that all equipment is electrically earthed. Keep container tightly closed.
- Specific uses** : Refer to technical data sheet available on request.
- Unsuitable packaging materials** : None known.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Engineering Controls** : Ventilation : Refer to Section 7

#### Exposure controls for hazardous components

Name	CAS-No.	Exposure Limits
Trimethoxyphenylsilane	2996-92-1	200 ppm TWA, 250 ppm STEL as methanol
Dibutyltin dilaurate	77-58-7	0.2 mg/m <sup>3</sup> STEL as Sn 0.1 mg/m <sup>3</sup> TWA as Sn
Tetramethyl orthosilicate	681-84-5	5 ppm STEL 1 ppm TWA 32 mg/m <sup>3</sup> STEL 6.3 mg/m <sup>3</sup> TWA
Methanol	67-56-1	250 ppm STEL 200 ppm TWA 333 mg/m <sup>3</sup> STEL 266 mg/m <sup>3</sup> TWA

#### Personal protection equipment

- Respiratory protection** : Suitable respiratory protection should be worn if the product is used in large quantities, confined spaces or in other circumstances where the OEL may be approached or exceeded.
- Hand protection** : Chemical protective gloves should be worn: Silver shield(TM). 4H(TM). Regarding glove's breakthrough time...,contact your chemical protective glove supplier.
- Eye protection** : Face shield or safety goggles.
- Skin protection** : Wear impervious overalls in circumstances where significant skin contact can occur.



**SILASTIC(R) 81-R CURING AGENT**

<b>On skin contact</b>	:	Irritating.
<b>If inhaled</b> <sup>3</sup>	:	May cause dizziness, drowsiness, confusion, headaches, nausea, and at high concentrations, unconsciousness.
<b>On ingestion</b> <sup>3</sup>	:	Harmful if swallowed. Forms methanol and may cause serious injury to man at doses > 200 mg/kg.
<b>Other Health Hazard Information</b>	:	Product may emit formaldehyde vapours at temperatures above 150°C in the presence of air. Formaldehyde vapour is harmful by inhalation and irritating to eyes and respiratory system at breathing concentration less than one part per million (1 ppm).

<sup>1</sup> Based on product test data.

<sup>2</sup> Based on test data from similar products.

<sup>3</sup> This information is based either on test data, extrapolation from tests on similar materials, review of component data, or a combination of these sources.

**12. ECOLOGICAL INFORMATION****Environmental fate and distribution**

This product hydrolyses in water or wet soil, releasing alcohols and silicic acid.

**Ecotoxicity effects**

Harmful to aquatic organisms and may cause long-term adverse effects in the aquatic environment.

**Bioaccumulation** : Organotin compounds can bioaccumulate.

**Fate and effects in waste water treatment plants**

May cause adverse effects on bacteria.

**13. DISPOSAL CONSIDERATIONS**

**Product disposal** : Dispose of in accordance with local regulations.

**Packaging disposal** : Dispose of in accordance with local regulations.

## SILASTIC(R) 81-R CURING AGENT

## 14. TRANSPORT INFORMATION

**Road / Rail (ADR/RID)**

UN No. : 1993

Proper Shipping Name : FLAMMABLE LIQUID, N.O.S. (SPECIAL PROVISION 640 E)  
(Contains TETRAPROPYLORTHOSILICATE)

Class : 3

Packing group : III

Trem-Card : 30GF1-III

Labels : ADR DANGER LABEL MODEL NO 3

**Sea transport (IMDG)**

UN No. : 1993

Proper Shipping Name : FLAMMABLE LIQUID, N.O.S.  
(Contains TETRAPROPYLORTHOSILICATE)

Class : 3

Packing group : III

Medical First Aid Guide (MFAG) : REFER TO THE EMERGENCY ACTION TABLE OF MFAG

Emergency Schedule (EmS) : EMS F-E EMS S-E

Marine pollutant : DIBUTYLTIN DILAURATE

Labels : FLAMMABLE LIQUID  
MARINE POLLUTANT

**Air transport (IATA)**

UN No. : 1993

Proper Shipping Name : FLAMMABLE LIQUID, N.O.S.  
(Contains TETRAPROPYLORTHOSILICATE)

Class : 3

Packing group : III

Labels : FLAMMABLE LIQUID

**SILASTIC(R) 81-R CURING AGENT****15. REGULATORY INFORMATION****Labelling according to EEC Directive**

- Contains** : Trimethoxyphenylsilane
- Symbols** : Xn Harmful.
- R-phrases** : R10 Flammable.  
R22 Harmful if swallowed.  
R36/38 Irritating to eyes and skin.  
R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- S-phrases** : S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
S37 Wear suitable gloves.  
S51 Use only in well-ventilated areas.  
S61 Avoid release to the environment. Refer to special instructions/Safety data sheets.

**National legislation / regulations**

- Ozone depleting chemicals** : No ozone depleting chemicals are present or used in manufacture.

**Status**

- EINECS** : All ingredients listed or exempt.

**SILASTIC(R) 81-R CURING AGENT****16. OTHER INFORMATION**

This product safety data sheet was prepared in compliance with Commission Directive 91/155/EEC, 67/548/EEC and 1999/45/EC as well as their relevant amendments, on the approximation of laws, regulations and administrative provisions relative to the classification, packaging and labelling of dangerous substances and preparations.

It is the responsibility of persons in receipt of this Product Safety Data Sheet to ensure that the information contained herein is properly read and understood by all people who may use, handle, dispose or in any way come in contact with the product. If the recipient subsequently produces a formulation containing the Dow Corning product, it is the recipient's sole responsibility to ensure the transfer of all relevant information from the Dow Corning Product Safety Data Sheet to their own Product Safety Data Sheet in compliance with Commission Directive 1999/45/EC.

All information and instructions provided in this Safety Data Sheet (SDS) are based on the current state of scientific and technical knowledge at the date indicated on the present SDS. Dow Corning shall not be held responsible for any defect in the product covered by this SDS, should the existence of such defect not be detectable considering the current state of scientific and technical knowledge.

As stated above, this Safety Data Sheet has been prepared in compliance with applicable European law. If you purchase this material outside Europe, where compliance laws may differ, you should receive from your local Dow Corning supplier a SDS applicable to the country in which the product is sold and intended to be used. Please note that the appearance and content of the SDS may vary - even for the same product - between different countries, reflecting the different compliance requirements. Should you have any question, please refer to your local Dow Corning supplier.

**R20/21/22** Harmful by inhalation, in contact with skin and if swallowed., **R20/22** Harmful by inhalation and if swallowed., **R22** Harmful if swallowed., **R23/24/25** Toxic by inhalation, in contact with skin and if swallowed., **R25** Toxic if swallowed., **R36/38** Irritating to eyes and skin., **R39/23/24/25** Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed., **R51/53** Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.