

DOW CORNING 200(R) FLUID, 50 CST.**1. IDENTIFICATION OF THE SUBSTANCE AND OF THE COMPANY**

Trade name	:	DOW CORNING 200(R) FLUID, 50 CST.		
Company	:	Dow Corning S.A. Parc Industriel - Zone C B-7180 Seneffe Belgium		
Service	:	Dow Corning Central Europe	Tel: +49 6112371	Fax: +49 611237609
		Dow Corning Northern Europe	Tel: +44 1676528000	Fax: +44 1676528001
		Dow Corning Southern Europe	Tel: +33 472841360	Fax: +33 472841379
Emergency Phone Number	:	Dow Corning (Barry U.K. 24h)	Tel: +44 1446732350	
		Dow Corning (Wiesbaden 24h)	Tel: +49 61122158	
		Dow Corning (Seneffe 24h)	Tel: +32 64 888240	

2. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical characterization: Silicone

Hazardous Ingredients:

Name	CAS-No.	EINECS/ ELINCS No.	Conc. (% w/w)	Classification
No hazardous ingredients.				

3. HAZARDS IDENTIFICATION

Not hazardous according to Council Directive 1999/45/EC and its subsequent amendments.

4. FIRST AID MEASURES

On contact with eyes	:	No first aid should be needed.
On skin contact	:	No first aid should be needed.
If inhaled	:	No first aid should be needed.
On ingestion	:	No first aid should be needed.

5. FIRE FIGHTING MEASURES

DOW CORNING 200(R) FLUID, 50 CST.

Suitable extinguishing media	:	Carbon dioxide, foam, dry powder or fine water spray. Water can be used to cool fire exposed containers.
Unsuitable extinguishing media	:	None known.
Hazards during fire fighting	:	None known.
Special protective equipment/procedures	:	A self-contained respirator and protective clothing should be worn. Keep containers cool with water spray until well after the fire is out. Determine the need to evacuate or isolate the area according to your local emergency plan.
Hazardous Combustion Products	:	Silica. Carbon oxides and traces of incompletely burned carbon compounds. Formaldehyde.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions	:	Wear proper protective equipment.
Precautions to protect the environment	:	Prevent from spreading or entering into drains, ditches or rivers by using sand, earth or other appropriate barriers.
Methods for cleaning up	:	Determine the need to evacuate or isolate the area according to your local emergency plan. Very large spills should be contained by bunding, etc... procedures. Mop, wipe or soak up with absorbent material and place in a container with a lid. The spilled product produces an extremely slippery surface.

7. HANDLING AND STORAGE

Advice on safe handling	:	Avoid eye contact. General ventilation is recommended.
Advice on storage	:	Do not store with oxidizing agents.
Specific uses	:	Refer to technical data sheet available on request.
Unsuitable packaging materials	:	None known.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls : Ventilation : Refer to Section 7

Exposure controls for hazardous components

Name	CAS-No.	Exposure Limits
------	---------	-----------------

None of the components have assigned exposure limits.

DOW CORNING 200(R) FLUID, 50 CST.

Materials to avoid : Can react with strong oxidising agents.

Hazardous decomposition products : See section 11.

11. TOXICOLOGICAL INFORMATION

On contact with eyes : May cause temporary discomfort.

On skin contact : No adverse effects are normally expected.

If inhaled : No adverse effects are normally expected.

On ingestion : No adverse effects are normally expected.

Other Health Hazard Information : Product may emit formaldehyde vapours at temperatures above 150°C in the presence of air. Formaldehyde vapour is harmful by inhalation and irritating to eyes and respiratory system at breathing concentration less than one part per million (1 ppm).

¹ Based on product test data.

² Based on test data from similar products.

12. ECOLOGICAL INFORMATION**Environmental fate and distribution**

Siloxanes are removed from water by sedimentation or binding to sewage sludge. In soil, siloxanes are degraded.

Ecotoxicity effects

No adverse effects on aquatic organisms.

Bioaccumulation : No bioaccumulation potential.

Fate and effects in waste water treatment plants

Removed > 90% by binding onto sewage sludge. No adverse effects on bacteria. The siloxanes in this product do not contribute to the BOD.

Additional environmental information

Additional environmental information on the silicone component is available on request.

13. DISPOSAL CONSIDERATIONS

Product disposal : Dispose of in accordance with local regulations.

Packaging disposal : Dispose of in accordance with local regulations.

DOW CORNING 200(R) FLUID, 50 CST.**14. TRANSPORT INFORMATION****Road / Rail (ADR/RID)**

Not subject to ADR/RID.

Sea transport (IMDG)

Not subject to IMDG code.

Air transport (IATA)

Not subject to IATA regulations.

15. REGULATORY INFORMATION**Labelling according to EEC Directive**

No special packaging or labelling requirements.

National legislation / regulations

Ozone depleting chemicals : No ozone depleting chemicals are present or used in manufacture.

Status

EINECS : All ingredients listed or exempt.

TSCA : All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

DOW CORNING 200(R) FLUID, 50 CST.**16. OTHER INFORMATION**

This product safety data sheet was prepared in compliance with Commission Directive 91/155/EEC, 67/548/EEC and 1999/45/EC as well as their relevant amendments, on the approximation of laws, regulations and administrative provisions relative to the classification, packaging and labelling of dangerous substances and preparations.

It is the responsibility of persons in receipt of this Product Safety Data Sheet to ensure that the information contained herein is properly read and understood by all people who may use, handle, dispose or in any way come in contact with the product. If the recipient subsequently produces a formulation containing the Dow Corning product, it is the recipient's sole responsibility to ensure the transfer of all relevant information from the Dow Corning Product Safety Data Sheet to their own Product Safety Data Sheet in compliance with Commission Directive 1999/45/EC.

All information and instructions provided in this Safety Data Sheet (SDS) are based on the current state of scientific and technical knowledge at the date indicated on the present SDS. Dow Corning shall not be held responsible for any defect in the product covered by this SDS, should the existence of such defect not be detectable considering the current state of scientific and technical knowledge.

As stated above, this Safety Data Sheet has been prepared in compliance with applicable European law. If you purchase this material outside Europe, where compliance laws may differ, you should receive from your local Dow Corning supplier a SDS applicable to the country in which the product is sold and intended to be used. Please note that the appearance and content of the SDS may vary - even for the same product - between different countries, reflecting the different compliance requirements. Should you have any question, please refer to your local Dow Corning supplier.